



Form 100 – Reroofing Installation Summary Form

Asphalt Shingles or Wood Shakes/Shingles

(NEW CONSTRUCTION – INCLUDE FORM 200 IF “REVISION” OR ROOFING SUB-PERMIT” IS REQUIRED ON THE PLANS FOR A NEW STRUCTURE)

Site Address: _____

Sloped Roof Pitch _____/12 Mean Roof Height _____ft Sloped Roof Area (SQRs) _____

Aerial Depiction of Structure is included (per Google Earth, Pictometry, Eagle View etc.)

****SUPPLEMENTAL Details and Information (identify all items related to the site-specific conditions)**

- MANDATED RETROFITS-Existing Wood decks, include **Mandated Roof-to-Wall Connection Retrofit** Form
- Tie-In Detail (FL LICENSED ENGINEER or ROOFING CONSULTANT) Repair (<25 ROOF AFEA – INCLUDE DETAILED SCOPE-OF-WORK)
- Re-Nail Deck (IF STRUCTURE WAS PERMITTED PRIOR TO 5/1/99) Sheath-over (ENGINEERING DETAILS ATTACHED)
- Re-cover (ONE ADDITIONAL LAYER ONLY/MUST BE ALLOWED BY PRODUCT APPROVAL)
- Skylights/Vents/etc. (REPLACEMENT ONLY) Provide FL or NOA # _____ (ATTACHED)
- FLAT Roof Deck portion included in Reroofing Scope (PROVIDE FORM 400-FLAT ROOF)

Underlayment Method & Material (Select One) FL or NOA # _____ (ATTACHED)

A	B	C	D	E
<input type="checkbox"/> Self-Adhered (Direct to Deck) **NOT an Option for Wood Shake/Shingle**	<input type="checkbox"/> 4” Wide Strip (ASTM D1970) Over all Joints/Seams (Per Table R905.1.1.1)	<input type="checkbox"/> 3 ¾” Wide Strip (AAMA 711) Over all Joints/Seams Per Table (R905.1.1.1)	<input type="checkbox"/> 2 Layers of 30# Felt (ASTM Approved)	<input type="checkbox"/> 2 Layers Synthetic U/L **NOT an Option for Wood Shake/Shingle
Self-Adhered (ASTM D1970) Polymer-Modified Bitumen Underlayment Applied directly to entire roof deck	4” Wide Strip of self-adhering polymer-modified bitumen membrane per ASTM D1970 applied over all joints with 30# felt on top	3 ¾” Wide Strip of self-adhering flexible flashing tape per AAMA 711 applied over all joints with 30# felt on top	Two layers of ASTM D226 Type II or ASTM D4869 Type II or IV; Layers to be lapped at 19” OC	Two layers of reinforced synthetic underlayment (Provide FL/NOA) Layer to be lapped by mi. half width of rolls

Product Specifications

Manufacturer	Product Name	Material Type	NOA or FL Approval #

Applicant’s Affidavit: I hereby certify that I have read the material on all pages of this document and have FULLY provided ALL the information requested.

Qualifier Name

Qualifier Signature

Date

SIMPLIFIED ROOF UPLIFT CHART FOR ROOFING APPLICATIONS

This simplified chart represents the worst-case wind pressures for the various roof slopes and heights. This chart is based on a Tributary Area = 10 SF which is required for roofing applications. If the roof height is less than 30 feet, but not exactly 15, 20, or 25 feet, you will need to go to the next higher roof height. If your roof is higher than 30 feet, these charts do not apply. Refer to Roof Chart Diagrams on Page 1 for Roof Zone Locations.

MEAN ROOF HEIGHT = 15 FEET

Flat Roof		Gable Roof			Hip Roof			
		1.51 to 4:12		4.1 to 6:12	6.1 to 12:12	1.51 to 4:12		4.1 to 6:12
Positive*	15.4/38.0	Positive 23.2		Positive 23.2	Positive 34.7	Positive 28.3		Positive 28.3
Zone		Zone	Roof	Roof	Roof	Zone	Roof	Roof
1	-60.5	1, 2e	-70.1	-54	-63.7	1	-63.7	-50.8
1'	-34.8	2n & 2r	-102	-86.2	-70.1	2e	-89.4	-70.1
2	-79.8	3e	-102	-86.2	-86.7	2r	-83	-70.1
3*	-109	3r	-102	-102	-70.1	3	-89.4	-70.1

MEAN ROOF HEIGHT = 20 FEET

Flat Roof		Gable Roof			Hip Roof			
		1.51 to 4:12		4.1 to 6:12	6.1 to 12:12	1.51 to 4:12		4.1 to 6:12
Positive*	16.4/40.3	Positive 24.6		Positive 24.6	Positive 36.9	Positive 30.1		Positive 30.1
Zone		Zone	Roof	Roof	Roof	Zone	Roof	Roof
1	-64.2	1, 2e	-74.5	-57.4	-67.7	1	-67.6	-54
1'	-36.9	2n & 2r	-109	-91.5	-74.5	2e	-95	-74.5
2	-84.8	3e	-109	-91.5	-92.1	2r	-88.1	-74.5
3*	-116	3r	-129	-108	-74.5	3	-95	-74.5

MEAN ROOF HEIGHT = 25 FEET


Flat Roof		Gable Roof			Hip Roof			
		1.51 to 4:12		4.1 to 6:12	6.1 to 12:12	1.51 to 4:12		4.1 to 6:12
Positive*	17.2/42.3	Positive 25.8		Positive 25.8	Positive 38.7	Positive 31.5		Positive 31.5
Zone		Zone	Roof	Roof	Roof	Zone	Roof	Roof
1	-67.3	1, 2e	-78.1	-60.2	-70.9	1	-70.9	-58.6
1'	-38.7	2n & 2r	-114	-96	-78.1	2e	-99.6	-78.1
2	-88.8	3e	-114	-96	-96.6	2r	-92.4	-78.1
3*	-121	3r	-135	-113	-78.1	3	-99.6	-78.1

MEAN ROOF HEIGHT = 30 FEET

Flat Roof		Gable Roof			Hip Roof			
		1.51 to 4:12		4.1 to 6:12	6.1 to 12:12	1.51 to 4:12		4.1 to 6:12
Positive*	17.9/43.9	Positive 26.8		Positive 26.8	Positive 40.2	Positive 32.8		Positive 32.8
Zone		Zone	Roof	Roof	Roof	Zone	Roof	Roof
1	-70	1, 2e	-81.1	-62.6	-73.7	1	-73.7	-58.8
1'	-40.2	2n & 2r	-118	-99.8	-81.1	2e	-103	-81.1
2	-92.3	3e	-118	-99.8	-100	2r	-96	-81.1
3*	-126	3r	-141	-118	-81.1	3	-103	-81.1

**If Parapet >= 3ft occurs around entire building use the same Zone 2 pressure for Zone 3 and use the higher positive pressure shown.*

Underlayment Options (CIRCLE One)




*Self-adhering polymer modified bitumen membrane complying with ASTM D1970 applied over the entire roof. All laps to be in accordance with the manufacturer's installation instructions.

Source: FEMA Hurricane Michael in Florida Recovery Advisory 2

Sealed Roof Deck Option A

[NOTE: A is NOT an Option for Wood Shake/Shingle]



** One layer of ASTM D226 Type II, ASTM D4889 Type IV, or ASTM D6757

*4-inch-wide (minimum) self-adhering modified bitumen tape at sheathing joints

4 feet x 8 feet roof sheathing

12 inches on center

6 inches on center

4 inches

6-inch end laps

Stagger rows

Fascia

Metal drip edge


Annular ring or deformed shank nails with metal or plastic caps. Cap diameter not less than 1 inch. Nail shank diameter not less than 0.083 inch. Metal cap thickness not less than 32-gage sheet metal or 0.01 inch for power-driver fasteners. Plastic cap outside edge thickness not less than 0.035 inch.

Source: FEMA Hurricane Michael in Florida Recovery Advisory 2

*3 3/4 inch AAMA 711 flashing tape is also permitted.

**Synthetic underlayment meeting the performance requirements specified in Option E may also be used.

Sealed Roof Deck Option B or C



**Two layers of ASTM D226 Type II or ASTM D4889 Type BI or IV

Metal drip edge

12-inch on center in the field

2 inches

6-inch on center at side and end laps

Fascia

19 inches

36 inches

36 inches

End laps shall be 6 inches

Annular ring or deformed shank nails with metal or plastic caps. Cap diameter not less than 1 inch. Nail shank diameter not less than 0.083 inch. Metal cap thickness not less than 32-gage sheet metal or 0.01 inch for power-driver fasteners. Plastic cap outside edge thickness not less than 0.035 inch.

Source: FEMA Hurricane Michael in Florida Recovery Advisory 2

*Synthetic underlayment meeting the performance requirements specified in Option E may also be used.

Sealed Roof Deck Option D or E

[NOTE: E is NOT an Option for Wood Shake/Shingle]

226 Cypress Lane, Palm Springs, FL 33461

Phone (561) 584-8200 x 8460

www.vpsfl.org



Village of Palm Springs
Planning, Zoning & Building
226 Cypress Lane
Palm Springs, FL 33461
Phone (561) 584-8200 x8460
www.vpsfl.org

ASBESTOS NOTIFICATION STATEMENT
(Required for **ALL** Demolitions and/or Renovations)

Per the Florida Building Code 105.9, each permit for the demolition or renovation of an existing structure shall contain an asbestos notification statement. The statement must indicate the owner's/operator's responsibility to comply with the provisions of Florida Statute 469.003. The owner/operator must notify the Palm Beach County Health Department of the intention to remove asbestos, when applicable, in accordance with state and federal law.

Written notification is required to be submitted to the Palm Beach County Health Department ten (10) working days prior to the commencement of any demolition or regulated renovation activity pursuant to Section 469 Florida Statutes.

For further information please contact:

Palm Beach County Health Department
Asbestos Program Coordinator
Air Pollution Control
800 Clematis Street
West Palm Beach, FL 33402
(561) 837-5900

By signing the application and permit for construction you certify that you have complied, or will comply with all Federal, State, and local laws and regulations pertaining to asbestos. You further understand that any violations of these requirements can result in monetary penalties to the building owners, lessees and their respective contractors. Additional penalties for failing to comply with asbestos rules may include criminal prosecution under federal law and contractor license forfeit/suspension under state law.

Job Address: _____

Company Name: _____

License #: _____ Phone #: _____

Permit #: _____ Date: _____

Applicants Signature: _____

Applicants Name Printed: _____



Village of Palm Springs

226 Cypress Lane
Palm Springs, FL 33461
Phone (561) 584-8200 x8460
www.vpsfl.org

SECTION 1524

WINDBORNE DEBRIS REGION – REQUIRED OWNERS NOTIFICATION FOR ROOFING CONSIDERATIONS

It is the responsibility of the roofing contractor to provide the owner with the required roofing permit, and to explain to the owner the content of this section. The provisions of Chapter 15 of the *Florida Building Code, Building (and Chapter 6 of the Florida Existing Building Code)* govern the minimum requirements and standards of the industry for roofing system installations. Additionally, the following items should be addressed as part of the agreement between the owner and the contractor. The owner's initial in the designated space indicates that the item has been explained.

1. Aesthetics – workmanship: The provisions of Chapter 15 (Roof Assemblies) are for the purpose of providing that the roofing system meets the wind resistance and water intrusion performance standards. Aesthetics (appearance) are not a consideration with respect workmanship provisions. Aesthetic issues such as color or architectural appearance, that not part of a zoning code, should be addressed as part of the agreement between the and the

2. Rerailing wood decks: When replacing roofing, the existing wood roof deck has to be rerailed in accordance with the current provisions of Chapter 16 (Structural Design) of the Florida Building Code. (The roof deck is usually concealed prior to removing the existing roof system).

3. Common roofs: Common roofs are those which have no visible delineation between neighboring units (i.e. townhouses, condominiums, etc.). In buildings with common roofs, the roofing contractor and/or owner should notify the occupants of adjacent units of roofing work to be performed.

4. Exposed ceilings: Exposed, open beam ceilings are where the underside of the roof decking can be viewed from below. The owner may wish to maintain the architectural appearance; therefore, roofing nail penetrations of the underside of the decking may not be acceptable. The owner provides the option of maintaining this appearance.

5. Ponding Water: The current roof system and/or deck of the building may not drain well and may cause water to pond (accumulate) in low-lying areas of the roof. Ponding can be an indication of structural distress and may require the review of a professional structural engineer. Ponding may shorten the life expectancy and performance of the new roofing system. Ponding conditions may not be evident until the original roofing system is removed. Ponding conditions should be corrected.

6. Overflow scuppers (wall outlets): It is required that rainwater flows off so that the roof is not overloaded from a build-up of water. Perimeter/edge walls or other roof extensions may block this discharge if overflow scuppers (wall outlets) are not provided. It may be necessary to install overflow scuppers in accordance with the requirements of: Chapter 6 of the *Florida Existing Building Code* and 15 of the *Florida Building Code* and the *Florida Building Code, Plumbing*.

7. Ventilation: Most roof structures should have some ability to vent natural airflow through the interior of the structural assembly (the building itself). The existing amount of attic ventilation shall not be reduced. **Exception:** Attic spaces, designed by a Florida-licensed engineer or registered architect to eliminate the attic venting, venting shall not be required.

Owner's/Agent's Signature:

Date:

 / /

Contractor's Signature:

Permit Number:

Property Address: